

Workshop on Reliable and Interactable

World Models

Where Is Motion From? Scalable Motion Attribution for Video Generation Models

Xindi Wu^{1, 2}, Despoina Paschalidou¹, Jun Gao¹, Antonio Torralba³, Laura Leal-Taixé¹, Olga Russakovsky², Sanja Fidler¹, Jonathan Lorraine¹ ¹NVIDIA, ²Princeton University, ³MIT CSAIL



Motivation

Despite rapid progress in video generation, how data shapes motion quality remains poorly understood.

Scale

Modern,

large-scale

models &

datasets

Key Goals

Focus on **Efficiently** Motion

Separate motion from static appearance Curation

Identify clips that improve motion quality

Guide

Our Solution: MOTIVE

MOtion Training Influence for Video gEneration

Problem Formulation

Given a query video and finetuning dataset, assign each training clip a motion-aware influence **score** to quantify its contribution to target generation

Method Components


1. Efficient Motion Gradient Computation


- Single-Sample Estimator
- Structured Projections (Fastfood)

2. Motion Attribution

- Detect motion between frames w. AllTracker
- Create motion magnitude patches highlighting dynamic areas
- · Apply motion-weighted loss to focus on moving regions and compute motion-specific gradients


Which training clips drive the motion in a video generation sample?






Motion-gradient computation has three steps: (1) detect motion with AllTracker; (2) compute motion-magnitude patches; (3) apply lossspace motion masks to focus gradients on dynamic regions.


MOTIVE: A scalable, gradient-based, motion-centric data attribution framework for video generation models



Motion Attribution Samples



Qualitative Results



Free Fall

Quantitative Results

VBench Evaluation

Method	Motion Smooth.	Dynamic Deg.
Base	96.3	82.3
Full FT	96.3	84.7
Random 10%	96.3	81.6
Ours w/o mask	96.3	85.3
MOTIVE	96.3	89.4

√ Maintains smoothness, improves dynamics with only

Why Motion Masking?

Without: 85.3%

With: 89.4% (+4.1%)

Human Evaluation

76.7% win vs. Base: 66.7% win vs. Random: vs. Full FT: 57.5% win

Ablation Findings

Single Timestep: t=500 achieves 68% agreement. Projection: D'=512 reaches 74.7% Spearman ρ.

Conclusion

First motion-centric attribution framework for video generation

Scalable via projection & majority voting

76.7% human preference vs. baseline with 10% data; Motion masking: +4.1% Dynamic Degree